

Installing **FLEXI-TILE** Interlocking Floor Tiles

The Flexi-Tile interlocking floor tile is easy to cut and lay, giving you endless possibilities to create an interior with your own personal touch. Flexi-Tile should be acclimatised to and installed in similar conditions to those which prevail during normal occupation of the room for 24 hours. In some cases where there are extreme variances in temperature or direct sun light Flex-Tile may need to be adhered to the sub floor. We recommend using a suitable vinyl adhesive.

Pre-Installation Checklist

- Clean, Level and Firm Subfloor.
- Sharp Knife, Fitted with a Heavy Duty Blade.
- Pencil or Chalk Marker.
- Straight Edge.
- A Rubber Mallet.
- Cutting Board and Tape Measure.

Areas of Use for Flexi-Tile



1

Start by making sure your subfloor is clean, level and firm.



2

Measure the length and width of the room and divide the dimensions in two. Locate and mark the centre of the room. This is the approximate starting point for the installation. Check the number of full tiles and the width of part tiles required to reach the walls in each direction.



3

The tiles are designed to fit tightly together. Use a rubber mallet to hammer the tiles into position. On reaching the walls, cut the edge tiles so as to leave 1/4in wide gap between tiles and the wall.



4

Cutting the edge tiles should be done with a sharp blade. A good non-slip straightedge should be used. It is better to make several light cuts than one heavy cut. Always cut the tile from the front. A cutting board should be used to prevent damage.